PREMIER HOSE TECHNOLOGIES

STEAM MANITOBA EN ISO 6134

Steam hose for 165°C

Standards: EN ISO 6134/05 type 1 class A.
Application: softwall steam hose, textile reinforced, recommended for use with saturated steam at a maximum working pressure of 6 bar (90 psi).
Temperature: from -40°C (-40°F) to +165°C (+329°F).

Construction

Tube: black, smooth, EPDM rubber, resistant to saturated steam.
Reinforcement: high strength synthetic cord.
Cover: black, smooth (wrapped finish), EPDM rubber, resistant to high temperatures, weathering and ozone.
Branding: continuous embossed marking "IVG – EN ISO 6134:2005 - 1A - STEAM - 6 bar - 165°C - I.D. - M - quarter and year of manufacture.
Also available upon request: 1.Different diameters 2.Cover in different colours.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1421832	10	25/64	21,5	0,85	6	90	60	900	0,31	0,21	120	400
1421859	13	1/2	25	0,99	6	90	60	900	0,37	0,25	120	400
1421840	16	5/8	30	1,18	6	90	60	900	0,55	0,37	120	400
1430130	19	3/4	33	1,30	6	90	60	900	0,62	0,42	120	400
1431366	25	1	40	1,58	6	90	60	900	0,77	0,52	120	400

ivg colbachini spa

00 44 1772 851370 sales@hosetechnologies.com www.hosetechnologies.com