



## WATER DAVIS



## Agricultural spraying hose

**Application:** softwall hose for agricultural spraying operation of water and insecticides or herbicides.

**Temperature:** from -25°C (-13°F) to +70°C (+158°F).

### Construction

**Tube:** black, smooth, SBR rubber.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth (wrapped finish), EPDM rubber, weathering and ozone resistant.

**Branding:** continuous green stripe “IVG Water (family logo)...”.

**Also available upon request:** 1.Different diameters 2.Cover in different colours 3.Different working pressures.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1206354	8	5/16	17	0,67	75	1125	225	3375	0,21	0,14	120	400
1045300	10	25/64	19	0,75	50	750	150	2250	0,24	0,16	120	400
1045423	10	25/64	19	0,75	75	1125	225	3375	0,24	0,16	120	400
1045431	10	25/64	21	0,83	75	1125	225	3375	0,32	0,21	120	400
1250060	13	1/2	23,5	0,93	75	1125	225	3375	0,37	0,25	120	400
1161024	16	5/8	28	1,10	75	1125	225	3375	0,51	0,34	120	400
1020846	19	3/4	31,5	1,24	75	1125	225	3375	0,59	0,40	120	400
1017705	25	1	37	1,46	20	300	60	900	0,77	0,52	120	400
1324993	25	1	39	1,54	75	1125	225	3375	0,81	0,54	120	400
1136054	35	1-3/8	48	1,89	20	300	60	900	1,10	0,74	120	400