


WATER OSLO 18



Lay flat water discharge hose

Application: lightweight and lay flat softwall hose, used for the discharge of industrial or waste waters in submerged pumps and in mobile irrigation systems.

Temperature: from -25°C (-13°F) to +70°C (+158°F).

Construction

Tube: black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

Branding: continuous green stripe "IVG Water (family logo)...".

Also available upon request: 1.Different diameters 2.Cover in different colours 3.Different working pressures.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1135317	51	2	58	2,29	18	270	54	810	0,68	0,45	120	400
1111345	80	3-5/32	90	3,55	18	270	54	810	1,49	1,00	120	400
1145479	90	3-35/64	100	3,94	18	270	54	810	1,66	1,12	120	400
1144812	100	3-15/16	112	4,41	18	270	54	810	2,26	1,52	120	400
1210360	102	4	114	4,49	18	270	54	810	2,29	1,54	120	400
1399187	120	4-23/32	132	5,20	18	270	54	810	2,69	1,80	120	400
1230549	152	6	166	6,54	18	270	54	810	3,89	2,61	120	400