




WATER TORONTO



Water suction and discharge hose

Application: hardwall hose for suction and discharge of water and non corrosive fluids. Suitable for agricultural, industrial and other applications.

Temperature: from -30°C (-22°F) to +70°C (+158°F).

Construction

Tube: black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord and helix wire.

Cover: black, smooth, (wrapped finish) synthetic rubber, weathering and ozone resistant.

Branding: continuous green stripe “IVG Water (family logo)...”.

Also available upon request: 1.Toronto/reel: suitable to be rolled up on reel 2. Different diameters 3.Cover in different colours.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1402102	30	1-3/16	38	1,50	10	150	30	450	0,58	0,39	150	5,9	0,9	120	400
1403648	32	1-1/4	40	1,58	10	150	30	450	0,63	0,42	160	6,3	0,9	120	400
1402110	38	1-1/2	47,5	1,87	10	150	30	450	0,83	0,56	190	7,5	0,9	120	400
1403079	40	1-3/7/64	49,5	1,95	10	150	30	450	0,86	0,58	200	7,9	0,9	120	400
1400614	51	2	60,5	2,38	10	150	30	450	1,12	0,75	255	10,0	0,9	120	400
1402153	63,5	2-1/2	75	2,96	10	150	30	450	1,80	1,21	380	15,0	0,9	120	400
1400495	76	3	87	3,43	10	150	30	450	2,06	1,38	455	17,9	0,9	120	400
1401688	80	3-5/32	91,5	3,61	10	150	30	450	2,27	1,52	480	18,9	0,9	120	400
1401343	90	3-35/64	103	4,06	10	150	30	450	3,50	2,35	540	21,3	0,9	120	400
1400525	102	4	114	4,49	10	150	30	450	3,68	2,47	610	24,0	0,9	120	400
1403664	120	4-23/32	136	5,36	10	150	30	450	4,99	3,35	660	26,0	0,9	60	200
1402552	127	5	143	5,63	10	150	30	450	5,14	3,45	700	27,6	0,9	60	200
1401386	152	6	170,5	6,72	10	150	30	450	7,27	4,88	1000	39,4	0,9	60	200
1406370	203	8	225	8,87	10	150	30	450	12,08	8,12	1400	55,2	0,9	60	200

