

VORTEX™ COUPLING STRAIGHT



Vortex[™] QRC Coupling with integral hose tail. Available for spares as a complete coupling or as individual spare parts.

VORTEX™ COUPLING 90 DEGREE



Vortex[™] QRC 90 °Coupling with integral hose tail. Available for spares as a complete coupling or as individual spare parts.

VORTEX™ SEAL KITS



All Vortex[™] Couplings are fully serviceable and easy to maintain.

A full range of Vortex[™] seal kits are available from stock.

VORTEX™ THREADED FITTINGS



Vortex[™] threaded fittings have an internally screwed hose tail which secures the Vortex[™] internal support spring in place, providing maximum support between the internal support spring and outer hose assembly, preventing the possibility of hose collapse vacuum/pressure.

Available with BSPT, BSPP and NPT thread form in mild steel or stainless steel.

VORTEX™ INTERNAL SUPPORT SPRING



Vortex[™] internal support spring prevents the outer silicone hose from collapsing whilst under vacuum/ pressure.

Available is open or closed coil form.

VORTEX™ HOSE FERRULE



Vortex[™] hose ferrules are strong but lightweight ferrules used to securely hold the coupling or fitting hose tail in place. The hose ferrule is crimped down to size using either a hand press or powered swaging machine.

VORTEX™ EXTERNAL SUPPORT SPRINGS



VortexTM external support springs provide support to the swaged area of the hose, preventing kinking of the most venerable are of the hose assembly.



Premier Hose Technologies Clifton Business Park, Preston New Road, Clifton, Preston PR4 0XQ, UK

Telephone +44 (1) 772 851370

sales@hosetechnologies.com www.hosetechnologies.com



