

AIR ALASKA



Steel wire compressed air hose

Application: high pressure steel wire reinforced compressed air hose; designed for applications where a heavy duty hose is necessary.

Temperature: from -30°C (-22°F) to +70°C (+158°F).

Construction

Tube: black, smooth, SBR rubber.

Reinforcement: inserts of steel wire.

Cover: yellow, smooth, (wrapped finish) long lasting EPDM rubber, weathering and ozone resistant.

Branding: continuous blue stripe “IVG Air (Family Logo)...”.

Also available upon request: 1.Hose cover according to MSHA specification 2.Different diameters 3.Black cover 4.Different working pressures 5.Tube resistant to oil mist traces 6.Version resistant to temperatures up to 100°C.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1282565	13	1/2	25,5	1,00	70	1050	210	3150	0,57	0,38	120	400
1282557	19	3/4	31,5	1,24	50	750	150	2250	0,75	0,50	120	400
1225740	25	1	37,5	1,48	45	675	135	2025	0,92	0,62	120	400
1290690	32	1-1/4	44,5	1,75	45	675	135	2025	1,21	0,82	120	400
1264176	38	1-1/2	51	2,01	45	675	135	2025	1,46	0,98	120	400
1359568	51	2	65	2,56	40	600	120	1800	1,97	1,32	120	400
1289012	63,5	2-1/2	80	3,15	35	525	105	1575	2,84	1,91	120	400
1359550	76	3	95	3,74	35	525	105	1575	4,33	2,91	120	400
1359541	102	4	121	4,77	30	450	90	1350	5,65	3,80	60	200