



## AIR MONTANA 27



# Compressed air hose

**Application:** softwall hose for compressed air with light traces of oil mist, normally used for heavy duty applications in road construction sites, quarries and mines.

**Temperature:** from -30°C (-22°F) to +70°C (+158°F).

### Construction








**Tube:** black, smooth, SBR rubber, oil mist resistant.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth, (wrapped finish) long lasting EPDM rubber, weathering and ozone resistant.

**Branding:** continuous blue brand “IVG Air (Family Logo)...”.

**Also available upon request:** 1.Different diameters 2.Cover in different colours 3.Different working pressures.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
												
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1026658	19	3/4	32	1,26	27	405	81	1215	0,67	0,45	120	397
1085255	19	3/4	30	1,18	27	405	81	1215	0,54	0,37	120	400
1026682	25	1	39	1,54	27	405	81	1215	0,90	0,60	120	400
1081411	25	1	37	1,46	27	405	81	1215	0,74	0,50	120	400
1021265	32	1-1/4	48	1,89	27	405	81	1215	1,27	0,86	120	400
1101722	32	1-1/4	46	1,81	27	405	81	1215	1,07	0,72	120	400
1021281	38	1-1/2	54,5	2,15	27	405	81	1215	1,52	1,02	120	400
1348655	51	2	70	2,76	27	405	81	1215	2,30	1,54	120	400
1219693	63,5	2-1/2	81,5	3,21	27	405	81	1215	2,60	1,75	120	400
1018930	76	3	96	3,78	27	405	81	1215	3,34	2,24	120	400
1250680	102	4	127	5,00	27	405	81	1215	5,01	3,37	120	400