



HOT FOODLAND



Hot water (10 bar W.P. 30 bar B.P) and steam hose (6 bar W.P. 60 bar B.P.)

Application: softwall hose for delivery of hot water and steam used to wash down in dairies, slaughterhouses and in the food industry in general.

Temperature: -30°C +95°C hot water, -30°C +165°C steam.

Construction


Tube: white, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord.

Cover: blue, smooth (wrapped finish), synthetic rubber, fatty food and weathering resistant.

Branding: continuous red stripe "IVG HOT (family logo)...".

Also available upon request: 1.Different diameters 2.White hose cover 3.Foodland/IIR with IIR tube in accordance to FDA title 21, item 177.2600 and BfR/XXI Cat.2 and cover in PVC/NBR, available in colours white/blue and white/white.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
 1401700	13	1/2	23	0,91	10	150	30	450	0,32	0,22	120	400
1402897	16	5/8	26	1,02	10	150	30	450	0,38	0,25	120	400
1401963	19	3/4	29	1,14	10	150	30	450	0,43	0,29	120	400
1400886	25	1	35	1,38	10	150	30	450	0,54	0,36	120	400
1415743	32	1-1/4	46,5	1,83	10	150	30	450	1,07	0,72	120	400
1425510	38	1-1/2	54	2,13	10	150	30	450	1,35	0,91	120	400
1401971	51	2	69,5	2,74	10	150	30	450	2,09	1,41	120	400

