


## HOT MULTIPLUS



### Hot water (10 bar W.P. 30 bar B.P) and steam hose (6 bar W.P. 60 bar B.P.)

**Standards:** Phthalates free. FDA tit. 21 item 177.2600 aqueous and fatty foods. BfR XXI Cat.2 foods.

**Application:** softwall hose for delivery of hot water and steam used to wash down in dairies, slaughterhouses and in the food industry in general.

**Temperature:** -30°C +95°C hot water. -30°C + 165°C steam.

**Construction**

**Tube:** white, smooth, IIR rubber.

**Reinforcement:** high strength synthetic cord.

**Cover:** blue, smooth (wrapped finish), synthetic rubber, fatty food and weathering resistant.

**Branding:** continuous red stripe "IVG HOT (family logo)...".

**Also available upon request:** 1. Different diameters.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1465457	5	12/61	12	0,47	10	150	30	450	0,12	0,08	120	400
1465465	8	5/16	16,5	0,65	10	150	30	450	0,20	0,14	120	400
1300001	13	1/2	23	0,91	10	150	30	450	0,32	0,22	120	400
1464272	16	5/8	26	1,02	10	150	30	450	0,40	0,27	120	400
1461168	19	3/4	29	1,14	10	150	30	450	0,46	0,31	120	400
1461176	25	1	35	1,38	10	150	30	450	0,57	0,39	120	400