



## STEAM VAPOFER



### Steam hose for 210°C

**Standards:** EN ISO 6134/05 type 2 class B (Ω).

**Application:** steel cord hose for saturated steam at a maximum working pressure 18 bar; it has an oil resistant cover. Used in the chemical industry, petrochemical and industrial applications in general. Not recommended for steam cleaner. The hose can be used for peaks of superheated steam at 230°C and at 18 bar. Attention: the use of superheated steam reduces the hose life. For longer life drain after use.

**Temperature:** from -40°C (-40°F) to +210°C (+410°F).

**Construction**

**Tube:** black, smooth, EPDM rubber, resistant to saturated steam.

**Reinforcement:** inserts of steel wire.

**Cover:** black, pin pricked, smooth (wrapped finish), synthetic rubber with excellent resistance to high temperatures, weathering, ageing and oils.

**Branding:** continuous embossed marking "IVG - EN ISO 6134:2005 - 2B - STEAM - 18 Bar - 210°C - D.I. - Ω - quarter and year of manufacture".

**Also available upon request:** 1.Vapofer/CSM, with red hypalon® cover  
2.According to the standard BS 5342 3.Different diameters.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1363603	13	1/2	27	1,06	18	270	180	2700	0,60	0,40	60	200
1335090	19	3/4	33,5	1,32	18	270	180	2700	0,86	0,58	60	200
1363581	25	1	40	1,58	18	270	180	2700	1,12	0,75	60	200
1363573	32	1/4	48	1,89	18	270	180	2700	1,40	0,94	60	200
1363646	38	1-1/2	54	2,13	18	270	180	2700	1,60	1,08	60	200
1363638	51	2	69	2,72	18	270	180	2700	2,57	1,73	60	200