


## WATER AMBURGO



### Water suction and discharge hose

**Application:** hardwall, corrugated hose for suction and discharge of water, non corrosive fluids, or natural liquid fertilizers; suitable for agricultural and industrial applications, for overhead irrigation systems or for tank truck use.

**Temperature:** from -30°C (-22°F) to +70°C (+158°F).

#### Construction

**Tube:** black, smooth, synthetic rubber, resistant to mud or sewage.

**Reinforcement:** high strength synthetic cord and helix wire.

**Cover:** black, corrugated (wrapped finish), synthetic rubber, weathering, ozone and ageing resistant.

**Branding:** continuous green stripe "IVG Water (family logo)...".

**Also available upon request:** 1. Different diameters 2. Different working pressures.

code	inside diameter		working pressure		burst pressure		weight nominal		bending radius		vacuum	length max	
	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm	inch	bar	m	ft
1019538	25	1	3	45	9	135	0,61	0,41	80	3,2	0,8	60	200
1019570	38	1-1/2	3	45	9	135	1,01	0,68	125	4,9	0,8	60	200
1019660	51	2	3	45	9	135	1,30	0,88	175	6,9	0,8	60	200
1019694	60	2-3/8	3	45	9	135	1,60	1,07	210	8,3	0,8	60	200
1019708	63,5	2-1/2	3	45	9	135	1,73	1,16	225	8,9	0,8	60	200
1019740	76	3	3	45	9	135	2,04	1,37	275	10,8	0,8	60	200
1450204	80	3-5/32	3	45	9	135	2,11	1,42	290	11,4	0,8	60	200
1019775	90	3-35/64	3	45	9	135	2,96	1,99	335	13,2	0,8	60	200
1413848	102	4	3	45	9	135	3,24	2,18	400	15,8	0,7	60	200
1439634	110	4-21/64	3	45	9	135	3,86	2,59	440	17,3	0,7	60	200
1413864	120	4-23/32	3	45	9	135	4,03	2,71	530	20,9	0,7	60	200
1002910	127	5	3	45	9	135	4,71	3,17	530	20,9	0,7	60	200
1413856	152	6	3	45	9	135	6,28	4,22	690	27,2	0,7	60	200
1442678	203	8	3	45	9	135	9,47	6,36	1010	39,8	0,7	60	200
1449370	254	10	3	45	9	135	11,73	7,88	1370	54,0	0,7	12	40