

## WATER LUWAS 30



### Multipurpose hose suitable for use in agriculture, car washes, industrial vehicles, compressors

**Standards:** flame retardant cover compound according to ASTM C-542.

**Application:** softwall hose of excellent quality, versatile, easy to handle and flexible, for delivery of compressed air, hot water, water mixed with additives such as fire fighting powders, insecticides, car washing shampoo, cooling water mixed with antifreeze.

**Temperature:** from -30°C (-22°F) to +100°C (+212°F).

**Construction**

**Tube:** black smooth synthetic rubber.

**Reinforcement:** high strength synthetic cord.

**Cover:** black, smooth (wrapped finish) synthetic rubber, self extinguishing, oils, weathering and ozone resistant.

**Branding:** yellow brand "IVG water(family logo) Luwas/30...".

**Also available upon request:** 1. Different diameters.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1307703	10	25/64	18	0,71	30	450	90	1350	0,21	0,14	120	400
1096451	13	1/2	21	0,83	30	450	90	1350	0,26	0,17	120	400
1456784	19	3/4	28	1,10	30	450	90	1350	0,40	0,27	120	400
1456792	25	1	35	1,38	30	450	90	1350	0,59	0,39	120	400
1458540	32	1-1/4	44	1,73	30	450	90	1350	0,91	0,61	120	400
1458558	38	1-1/2	51	2,01	30	450	90	1350	1,17	0,78	120	400
1380087	50	2	66	2,60	30	450	90	1350	1,82	1,22	120	400