


WATER OSLO 5



Lay flat water discharge hose

Application: lightweight and lay flat softwall hose, used for the discharge of industrial or waste waters in submerged pumps and in mobile irrigation systems.

Temperature: from -25°C (-13°F) to +70°C (+158°F).

Construction

Tube: black, smooth, synthetic rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), synthetic rubber, weathering and ozone resistant.

Branding: continuous green stripe “IVG Water (family logo)...”.

Also available upon request: 1.Different diameters 2.Cover in different colours 3.Different working pressures.

code	inside diameter		outside diameter		working pressure		burst pressure		weight nominal		length max	
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	m	ft
1168495	51	2	56,5	2,23	5	75	15	225	0,57	0,38	120	400
1168509	76	3	81,5	3,21	5	75	15	225	0,84	0,56	120	400
1071238	102	4	108	4,26	5	75	15	225	1,23	0,82	120	400
1071530	152	6	158	6,23	5	75	15	225	1,83	1,23	120	400
1210408	203	8	210	8,27	5	75	15	225	2,49	1,67	60	200
1095412	254	10	262	10,32	5	75	15	225	3,67	2,47	60	200
1388835	305	12	315	12,41	5	75	15	225	5,40	3,63	60	200